



RAVENOL STF Synchronesh Transmission Fluid

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221105

Oil type: Synthetic

Recommendations: Chrysler 4874464, Chrysler 4874465, Chrysler MS-9224, Chrysler MS-9417, GM 1052931, GM 12345349, GM 12345577, GM 12377916, GM 9985535, GM 9985648, GM 9986105

Application: Truck, Passenger car



RAVENOL STF Synchronesh Transmission Fluid is a full synthetic transmission oil based on high-quality synthetic base oils with a special additive treatment and inhibition ensuring trouble-free transmission function. This exceeds the needs of today's application requirements.

RAVENOL STF Synchronesh Transmission Fluid is a specially developed, modern transmission oil for manual transmissions and transfer cases by GM and Chrysler. Guarantees maximum wear protection under any operating conditions.

1L | 1221105-001

4L | 1221105-004

10L | 1221105-010

20L | 1221105-020

20L | 1221105-B20

60L | 1221105-060

60L | 1221105-D60

208L | 1221105-208

208L | 1221105-D28

Application instructions

RAVENOL STF Synchronesh Transmission Fluid is especially suited for the following GM and Chrysler manual transmissions and transfer gearboxes:

New Venture Gear NV T350, NV 1500, NV 2550, NV 3500, NV 3550, NV 5600

Chrysler NSG370 for Jeep Liberty 2005-2008, Jeep Wrangler 2005- , Chrysler Crossfire

Tremec T4, T5, T18, T56, T176, TKO500, TKO600, TR 3450 and TR 3550.

Not for use in hypoid gear rear axles or limited slip.

Characteristics

- A high pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming properties even at high speeds.
- Good shifting behaviour even in low temperatures, extremely low pour point.
- Extended life.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	7,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	36,5	DIN 51562-1
Viscosity Index VI		175	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	8.900	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	842,0	EN ISO 12185
Flashpoint	°C	216	DIN EN ISO 2592
Pourpoint	°C	-51	DIN ISO 3016