



RAVENOL TDG 75W-110



1L | 1221109-001

4L | 1221109-004

10L | 1221109-010

20L | 1221109-020

60L | 1221109-060

60L | 1221109-D60

208L | 1221109-208

208L | 1221109-D28

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221109

Viscosity: 75W-110

Specifications: API GL-4, API GL-5, API MT-1

Oil type: Full synthetic

Approvals: ZF TE-ML 05A (ZF008351), ZF TE-ML 12S (ZF008351), ZF TE-ML 16F (ZF008351), ZF TE-ML 21A (ZF008351)

Recommendations: DAF, IVECO, Mack GO-J, MIL -L-2105 D, MIL -PRF 2105 E, SAE J2360, Scania STO 2:0 A, ZF TE-ML 05B, ZF TE-ML 07A, ZF TE-ML 08, ZF TE-ML 19C, ZF TE-ML 21B

Application: Truck, Passenger car

RAVENOL TDG 75W-110 is full synthetic "Total Drive Line" low viscosity transmission oil.

RAVENOL TDG 75W-110 is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL TDG 75W-110 is oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks.

Application instructions

RAVENOL TDG 75W-110 is universal gear oil developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Characteristics

- Excellent thermal stability.
- High protection from rust, corrosion, foaming.
- Low solidification point.
- Excellent EP properties.
- Good shifting behaviour in low temperatures.
- Extended life.
- Fuel savings.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	21,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	163,5	DIN 51562-1
Viscosity Index VI		155	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	98.700	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	874,0	EN ISO 12185
Flashpoint	°C	216	DIN EN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016