



RAVENOL Getriebeoel PSA SAE 75W-80



1L | 1222100-001

4L | 1222100-004

10L | 1222100-010

20L | 1222100-020

20L | 1222100-B20

60L | 1222100-060

60L | 1222100-D60

208L | 1222100-208

208L | 1222100-D28

1000L | 1222100-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222100

Viscosity: 75W-80

Specifications: API GL-4

Oil type: Semi-synthetic

Recommendations: PSA B71 2315

Application: Passenger car

RAVENOL Getriebeoel PSA SAE 75W-80 is a high-quality solvent refined base oil based semi-synthetic multi-grade transmission oil with special EP (extreme pressure) properties.

RAVENOL Getriebeoel PSA SAE 75W-80 has a special formula for outstanding wear protection and lubrication properties.

Application instructions

RAVENOL Getriebeoel PSA SAE 75W-80 is used in manual shift transmissions requiring trouble-free lubrication.

RAVENOL Getriebeoel PSA SAE 75W-80 can be used in manual transmissions where the manufacturer specifies a low-viscosity oil.

Characteristics

- Outstanding oxidation protection.
- Low viscosity in low temperatures.
- Excellent wear protection.
- Enhanced EP properties.
- Good foaming properties.
- Neutral to sealants.
- Outstanding protection from rust and corrosion.

Technical Product Data

| CHARACTERISTICS | PROPERTY | DATA | AUDIT |
|--------------------------------|--------------------|-----------|-----------------|
| Colour | | hellbgebl | VISUELL |
| Viscosity at 100 °C | mm ² /s | 8,5 | DIN 51562-1 |
| Viscosity at 40 °C | mm ² /s | 43,1 | DIN 51562-1 |
| Viscosity Index VI | | 178 | DIN ISO 2909 |
| Brookfield Viscosity at -40 °C | mPa*s | 52.500 | ASTM D2983 |
| Copper Strip Test at 121 °C | | 1b | ASTM D130 |
| Density at 20 °C | kg/m ³ | 843,0 | EN ISO 12185 |
| Flashpoint | °C | 234 | DIN EN ISO 2592 |
| Pourpoint | °C | -39 | DIN ISO 3016 |