



# RAVENOL Getriebeoel LS SAE 75W-90



1L | 1222102-001  
4L | 1222102-004  
10L | 1222102-010  
20L | 1222102-020  
20L | 1222102-B20  
60L | 1222102-060  
60L | 1222102-D60  
208L | 1222102-208  
208L | 1222102-D28  
1000L | 1222102-700

**Kategorie:** Gear oil for manual transmissions and drive axis

**Artikelnummer:** 1222102

**Viscosity:** 75W-90

**Specifications:** API GL-5 + LS, MIL -L-2105 D

**Oil type:** Synthetic

**Recommendations:** GM 1940058, GM 88862624, GM 88862625, GM 93165388, ZF TE-ML 05C, ZF TE-ML 05D

**Application:** Truck, Passenger car

**RAVENOL Getriebeoel LS SAE 75W-90** is a synthetic lubricant for mechanical transmissions.

**RAVENOL Getriebeoel LS SAE 75W-90** is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

## Application instructions

**RAVENOL Getriebeoel LS SAE 75W-90** was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

## Characteristics

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	17,1	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	102,1	DIN 51562-1
Viscosity Index VI		182	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	84.300	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m <sup>3</sup>	839,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016