



RAVENOL Getriebeoel EPX SAE 85W-140 GL-5



1L | 1223211-001

4L | 1223211-004

10L | 1223211-010

20L | 1223211-020

20L | 1223211-B20

60L | 1223211-060

208L | 1223211-208

208L | 1223211-D28

1000L | 1223211-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1223211

Viscosity: 85W-140

Specifications: API GL-5, MIL -L-2105 D

Oil type: Mineral

Recommendations: CS 3000B, Ford M2C-9002 A, GM, Mack GO-G, MAN 342 M1, ZF TE-ML 05A, ZF TE-ML 16D, ZF TE-ML 21A

Application: Agricultural machinery, Passenger car, Truck

RAVENOL Getriebeoel EPX SAE 85W-140 GL-5 is a lubricating oil for mechanical gears based on high quality and solvent refined base oils. Special extreme pressure (EP)-active substances and selected additives give excellent lubricating oil properties.

RAVENOL Getriebeoel EPX SAE 85W-140 GL-5 is designed for use with maximum duty, hypoid gearing gears (axel drive, manual transmission, etc.), so far extreme pressure gear oils are required.

Application instructions

RAVENOL Getriebeoel EPX SAE 85W-140 GL-5 is designed for use in highly loaded, hypoid gears for hypoid gearbox, as well as for axle, transfer case, transmission gear, auxiliary gearboxes in vehicles and machinery and for use as extreme pressure gear oil where this grade of lubricant is specified by the manufacturer.

Characteristics

- a very good oxidation stability
- widest possible protection against rust and corrosion
- no foam formation
- excellent extreme pressure properties
- low pour point
- neutral behaviour towards metals and sealing materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	26,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	355,0	DIN 51562-1
Viscosity Index VI		99	DIN ISO 2909
Brookfield Viscosity at -12 °C	mPa*s	55.000	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	894,0	EN ISO 12185
Flashpoint	°C	224	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016