



RAVENOL Sperrdiff. Hyp. Getr.öl LS SAE 85W-90 GL-5



1L | 1223301-001
4L | 1223301-004
20L | 1223301-020
20L | 1223301-B20
60L | 1223301-060
208L | 1223301-208

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1223301

Viscosity: 85W-90

Specifications: API GL-5, MIL -L-2105 D

Oil type: Mineral

Recommendations: Ford Spezifikation, ZF TE-ML 05C, ZF TE-ML 12C, ZF TE-ML 16E

Application: Agricultural machinery, Passenger car, Truck

RAVENOL Sperrdiff. Hyp. Getr.öl LS SAE 85W-90 GL-5 offers best requirements in differential gears and differential lock.

RAVENOL Sperrdiff. Hyp. Getr.öl LS SAE 85W-90 GL-5 ensures good adhesion, high pressure-resistant lubricating film and offers excellent "limited slip" (LS) properties against unwanted slip-slip properties. Greatly offset hypoid gear pairs are also under severe operating conditions effectively protected against wear.

Application instructions

RAVENOL Sperrdiff. Hyp. Getr.öl LS SAE 85W-90 GL-5 was specially developed for use in differential with high requirements on differential with differential lock.

Characteristics

- Extremely high load carrying capacity
- Excellent wear protection by EP agents
- Excellent "limited slip" – Features
- Excellent resistance to aging
- High oxidation resistance even under high thermal stress
- Good foam / air separation and behave well at high speeds
- Neutrality towards non-ferrous metals and seals
- Excellent viscosity-temperature behavior

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	17,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	177,3	DIN 51562-1
Viscosity Index VI		108	DIN ISO 2909
Brookfield Viscosity at -12 °C	mPa*s	12.100	ASTM D2983
Copper Strip Test at 121 °C		1b	ASTM D130
Density at 20 °C	kg/m ³	889,0	EN ISO 12185
Flashpoint	°C	214	DIN EN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016