



RAVENOL STOU SAE 5W-30

Kategorie: Engine oil for agricultural vehicles and construct

Artikelnummer: 1310108

Viscosity: 5W-30

Specifications: ACEA E2, API CG-4, API GL-4

Recommendations: Allison C4, Caterpillar TO-2, DTFR 15B110 (MB 228.3), Ford ESN-M2C-159 B, John Deere J27, Massey Ferguson M1139, Massey Ferguson M1144, Massey Ferguson M1145, MB 227.1, MB 228.1, MB 228.3, MIL -L-2104 D, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06C, ZF TE-ML 06D, ZF TE-ML 07B

Application: Agricultural machinery

RAVENOL STOU SAE 5W-30 is a modern multi-purpose oil for agricultural machines, excavators and construction machines. It is made of high quality base oils and selected additives. It is a special oil, which meets the recommendations of all well-known field tractors.

RAVENOL STOU SAE 5W-30 is equally suited for engines, transmissions and hydraulic systems of modern tractors. High-quality base oils and selected additives ensure trouble-free operation of all units at all times of the year. Suitable for wet brakes and couplings (PTO couplings).

Application instructions

RAVENOL STOU SAE 5W-30 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 5W-30 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as transmission oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- A high and stable viscosity index
- An excellent extreme pressure properties



20L | 1310108-020

60L | 1310108-060

208L | 1310108-208

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,8	DIN 51575
tn	mg KOH/g	11,8	ASTM D2896
Viscosity at 100 °C	mm ² /s	11,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	70,8	DIN 51562-1
Viscosity Index VI		161	DIN ISO 2909
Density at 20 °C	kg/m ³	856,0	EN ISO 12185
Flashpoint	°C	228	DIN EN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016