



RAVENOL STOU SAE 10W-40

Kategorie: Engine oil for agricultural vehicles and construct

Artikelnummer: 1310111

Viscosity: 10W-40

Specifications: ACEA E3, API CG-4, API GL-4, API SF

Recommendations: 80W-90, 85W, 85W-90, ACEA E3, Allison C4, API CG-4/SF, API GL-4, Atlas Copco Kompressoren, Case IH-MS 1209, Caterpillar TO-2, DTFR 15B110 (MB 228.3), FENDT KDM 41.2011, Ford ESN-M2C-134 B, Ford ESN-M2C-134 C, Ford ESN-M2C-134 D, Ford ESN-M2C-159 B, Ford ESN-M2C-159 C, Getriebeöl: SAE 80W, Hydrauliköl: HVLP ISO VG 68-100, John Deere J20C, John Deere J27, Holman CompAir Kompressoren, MAN 271, Massey Ferguson M1139, Massey Ferguson M1144, Massey Ferguson M1145, MAT 3525, MB 227.1, MB 228.1, MB 228.3, MIL -L-2104 D, Motorenöl: SAE 10W-40, New Holland NH 410B, John Deere Spezialtraktorenöl: J20C, ZF TE-ML 06A, ZF TE-ML 06B, ZF TE-ML 06C, ZF TE-ML 06D, ZF TE-ML 07B

Application: Agricultural machinery



5L | 1310111-005

10L | 1310111-010

20L | 1310111-020

20L | 1310111-B20

60L | 1310111-060

208L | 1310111-208

208L | 1310111-D28

1000L | 1310111-700

RAVENOL STOU SAE 10W-40 is an up-to-date multifunctional lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils and additives.

RAVENOL STOU SAE 10W-40 meets the recommendations of all well known tractor manufacturers and is equal to use in engines, transmissions and hydraulic systems of modern tractors. Ensures trouble-free operation of all units in all seasons.

Application instructions

RAVENOL STOU SAE 10W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 10W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- A high and stable viscosity index
- An excellent extreme pressure properties

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,45	DIN 51575
tn	mg KOH/g	12,4	ASTM D2896
Viscosity at 100 °C	mm ² /s	14,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	101,1	DIN 51562-1
Viscosity Index VI		151	DIN ISO 2909
Density at 20 °C	kg/m ³	864,0	EN ISO 12185
Flashpoint	°C	234	DIN EN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016