



20L | 1310112-020  
20L | 1310112-B20  
60L | 1310112-060  
60L | 1310112-D60  
208L | 1310112-208  
1000L | 1310112-700

# RAVENOL STOU SAE 15W-30

**Kategorie:** Engine oil for agricultural vehicles and construct

**Artikelnummer:** 1310112

**Viscosity:** 15W-30

**Specifications:** ACEA E1/E2, API CE, API GL-4, API SF

**Recommendations:** Allison C4, Atlas Copco Kompressoren, Case International J I, Case MS 1118, Case MS 1206, Case MS 1209, Caterpillar TO-2, Fiat AF 87, Ford NH 024C, Ford NH 324B, Ford NH 540B, Ford Pumpentest, Getriebeöl: SAE 80W, Hydrauliköl: HLP ISO VG 68, International Harvester B6, John Deere J20C, John Deere J20D, Holman CompAir Kompressoren, Massey Ferguson M1127, Massey Ferguson M1139, Massey Ferguson M1144, MIL -L-2105, Parker Denison HF-2, John Deere Spezialtraktorenöl: J27A, Vickers Pumpentest, ZF TE-ML 06B, ZF TE-ML 07B

**Application:** Agricultural machinery

**RAVENOL STOU SAE 15W-30** is a multi-purpose super universal tractor oil for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers as listed below, and can be used in engines, transmissions and hydraulic systems of most equipment in all seasons which require this grade of oil.

## Application instructions

**RAVENOL STOU SAE 15W-30** has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes and PTO transmissions) and as a hydraulic oil where this specification of product is required. Can also be used as compressor oil.

## Characteristics

- Excellent viscosity-temperature behaviour
- Exceptional cold starting abilities
- Excellent detergent and dispersant properties
- High resistance to ageing

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,5	DIN 51575
tn	mg KOH/g	11,7	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	11,8	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	71,7	DIN 51562-1
Viscosity Index VI		159	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	861,0	EN ISO 12185
Flashpoint	°C	222	DIN EN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016