



20L | 1310114-020
20L | 1310114-B20
60L | 1310114-060
208L | 1310114-208
1000L | 1310114-700

RAVENOL STOU SAE 20W-40

Kategorie: Engine oil for agricultural vehicles and construct

Artikelnummer: 1310114

Viscosity: 20W-40

Specifications: ACEA E3, API CG-4, API GL-4, API SF

Recommendations: Allison C4, Caterpillar TO-2, Ford M2C-134 D, Ford M2C-159 C, Massey Ferguson CMS M1143, Massey Ferguson CMS M1144, Massey Ferguson CMS M1145, MB 227.1, MIL -L-2104 D, ZF TE-ML 06B, ZF TE-ML 07B

Application: Agricultural machinery

RAVENOL STOU SAE 20W-40 is up-to-date multifunctional STOU (Super Tractor Oil Universal) lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils. It is a special fluid which meets the recommendations of agricultural machinery manufacturers.

RAVENOL STOU SAE 20W-40 is equal to use in engines, transmissions and hydraulic systems of modern tractors. Top-grade solvent refined base oils and special synthetic based additives ensure trouble-free operation of all units in all seasons.

Application instructions

RAVENOL STOU SAE 20W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 20W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- Excellent extreme pressure properties
- A high and stable viscosity index

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	1,5	DIN 51575
tbn	mg KOH/g	13,0	ASTM D2896
Viscosity at 100 °C	mm ² /s	13,1	DIN 51562-1
Viscosity at 40 °C	mm ² /s	111,8	DIN 51562-1
Viscosity Index VI		112	DIN ISO 2909
CCS Viscosity at -15 °C	mPa*s	6860	ASTM D5293
Density at 20 °C	kg/m ³	883,0	EN ISO 12185
Flashpoint	°C	246	DIN EN ISO 2592
Pourpoint	°C	-30	DIN ISO 3016