



RAVENOL Hydraulikoel HLP-D 22

Kategorie: Other hydraulic oil

Artikelnummer: 1323303

Viscosity: 22

Specifications: DIN 51524-2

Oil type: Mineral

Recommendations: Daimler DBL 6721, MAN N 698, Parker Denison HF-0

Application: Industry



RAVENOL Hydraulikoel HLP-D 22 is detergent hydraulic oil with good net and cleaning effect.

RAVENOL Hydraulikoel HLP-D 22 is designed with selected base oils with additives to prevent corrosion, wear and friction.

RAVENOL Hydraulikoel HLP-D 22 also contains detergent and dispersing agents, which always provide for a clean hydraulic system. These additives dissolve contaminants, hold them in suspension and enabling the cleaning of contaminated hydraulic systems. The functional elements of a hydraulic system thereby remain free of deposits and bonds. This will emulsified penetrating water and ensure trouble-free operation of the hydraulic system.

5L | 1323303-005
20L | 1323303-020
20L | 1323303-B20
208L | 1323303-208
1000L | 1323303-700

Application instructions

RAVENOL Hydraulikoel HLP-D 22 is for use in agriculture hydraulic systems, construction machinery, cement factories, foundries, and electro-plate clutches. It can also be used as functional test oil, inlet oil for aggregates and machinery, textile machinery and machine tools.

Characteristics

- High aging resistance and high corrosion protection
- Good air release
- Excellent wear protection and proper conduct foam
- Very good viscosity-temperature behaviour
- neutral behaviour towards sealing materials
- Extremely good detergent and dispersant characteristics
- Excellent corrosion protection even at the ingress of wetness

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	4,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	23,0	DIN 51562-1
Viscosity Index VI		120	DIN ISO 2909
Density at 20 °C	kg/m ³	849,0	EN ISO 12185
Flashpoint	°C	200	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016