



RAVENOL ODL 68 Druckluftoel

Kategorie: Industrial oil

Artikelnummer: 1323406

Viscosity: 68

Recommendations: Atlas Copco Kompressoren, Bosch, Cress, DeWalt, Festo, Hilti, Hitachi, Makita, Ryobi, Seno, Sumake

Application: Industry

RAVENOL ODL 68 Druckluftoel is a special-compressed-air-oil for pneumatic tools of all systems.

RAVENOL ODL 68 Druckluftoel bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.



208L | 1323406-208

1000L | 1323406-700

Application instructions

RAVENOL ODL 68 Druckluftoel is specially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe. Please follow the manufacturer's instructions.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellgelb	VISUELL
Viscosity at 100 °C	mm ² /s	9,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	68,0	DIN 51562-1
Viscosity Index VI		106	DIN ISO 2909
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Flashpoint	°C	256	DIN EN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016