



20L | 1323407-020
20L | 1323407-B20
208L | 1323407-208
1000L | 1323407-700

RAVENOL ODL 100 Druckluftoil

Kategorie: Hydraulic oil

Artikelnummer: 1323407

Viscosity: 100

Oil type: Mineral

Recommendations: Atlas Copco Kompressoren, Bosch, Cress, DeWalt, Festo, Hilti, Hitachi, Makita, Ryobi, Seno, Sumake

Application: Industry

RAVENOL ODL 100 Druckluftoil is a special-compressed-air-oil for pneumatic tools of all systems.

RAVENOL ODL 100 Druckluftoil bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

Application instructions

RAVENOL ODL 100 Druckluftoil is especially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe.

Please follow the manufacturer's instructions.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a good adherence
- a high aging resistance
- a reliable wear protection
- an excellent corrosion protection
- neutrality of sealing materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	11,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	100,0	DIN 51562-1
Viscosity Index VI		105	DIN ISO 2909
Density at 20 °C	kg/m ³	875,0	EN ISO 12185
Flashpoint	°C	264	DIN EN ISO 2592
FZG-Test A/8.3/90 Damage loading step	%wt.	12	DIN 51354/2
Pourpoint	°C	-24	DIN ISO 3016