



RAVENOL Kompressoren-Oel VDL 150



1L | 1330101-001
5L | 1330101-005
10L | 1330101-010
20L | 1330101-020
20L | 1330101-B20
60L | 1330101-060
208L | 1330101-208
1000L | 1330101-700

Kategorie: Industrial oil

Artikelnummer: 1330101

Viscosity: 150

Specifications: DIN 51352-2, DIN 51506 VDL

Oil type: Mineral

Application: Industry

RAVENOL Kompressorenoel VDL 150 meets the high requirements of DIN 51506. Specifically designed with premium quality and age-resistant base oils.

RAVENOL Kompressorenoel VDL 150 has a good adhesion, is water repellent and wear-reducing. As many compressors operate at high temperatures, the oil should have good aging resistance at very low residue formation.

RAVENOL Kompressorenoel VDL 150 provides a secure lubrication not only in the upper temperature range, also in the cold state of the compressor to achieve a reduction of wear. By selected and coordinated additive composition the tendency to coking and the formation of flammable residues is minimized.

Application instructions

RAVENOL Kompressorenoel VDL 150 can be used in stationary and mobile compressors with discharge temperatures up to 220°C.

RAVENOL Kompressorenoel VDL 150 can also be used for circular lubrication of engines and diesel engines where the manufacturer does not stipulate any HD motor oil.

Characteristics

- Excellent aging resistance
- Best wear protection
- Excellent viscosity-temperature behavior
- Very good cold starting properties
- Low coking tendency

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Acid Number TAN	mgKOH/g	0,45	ASTM D664
Viscosity at 100 °C	mm ² /s	14,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	148,2	DIN 51562-1
Viscosity Index VI		97	DIN ISO 2909
Density at 20 °C	kg/m ³	885,0	EN ISO 12185
Flashpoint	°C	240	DIN EN ISO 2592
Pourpoint	°C	-20	DIN ISO 3016