



# RAVENOL SCR 32 Screw Kompressorenöl



5L | 1330304-005  
20L | 1330304-020  
60L | 1330304-060  
208L | 1330304-208

**Kategorie:** Industrial oil

**Artikelnummer:** 1330304

**Viscosity:** 32

**Specifications:** DIN 51524-2

**Oil type:** Mineral

**Application:** Industry

**RAVENOL SCR 32 Screw Kompressorenöl** is optimal alloyed mineral screw compressor oil, with a high performance level and a wide application area of the whole industry. It is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

## Application instructions

**RAVENOL SCR 32 Screw Kompressorenöl** is used in compressors.

## Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellgelb	VISUELL
Aging stability, TOST	st	2000	DIN 51587
Viscosity at 100 °C	mm <sup>2</sup> /s	5,8	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	32,1	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	848,0	EN ISO 12185
Flashpoint	°C	224	DIN EN ISO 2592
FZG-Test A/8.3/90 Damage loading step	%wt.	12	DIN 51354/2
Pourpoint	°C	-30	DIN ISO 3016