



# RAVENOL SCR 68 Screw Kompressorenöl



5L | 1330306-005  
20L | 1330306-020  
60L | 1330306-060  
208L | 1330306-208

**Kategorie:** Industrial oil

**Artikelnummer:** 1330306

**Viscosity:** 68

**Specifications:** DIN 51524-2

**Oil type:** Mineral

**Recommendations:** FZG-Test A 8,3/90, Sperry Vickers I-286-S, Sperry Vickers M-2950-S, Vickers Pumpentest

**Application:** Industry

**RAVENOL Screw Kompressorenöl SCR 68** is optimal alloyed, has a high performance level and a wide application area of the whole industry. It is characterised by a good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

## Application instructions

**RAVENOL Screw Kompressorenöl SCR 68** is used in compressors.

## Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellgelb	VISUELL
Aging stability, TOST	st	2000	DIN 51587
Damage loading step		12	DIN 51354/2
Viscosity at 100 °C	mm <sup>2</sup> /s	9,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	68,0	DIN 51562-1
Viscosity Index VI		106	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	866,0	EN ISO 12185
Flashpoint	°C	256	DIN EN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016