



RAVENOL SCR 100 Screw Kompressorenöl



208L | 1330307-208

Kategorie: Industrial oil

Artikelnummer: 1330307

Viscosity: 100

Specifications: DIN 51524-2, ISO 6743-4 HM

Recommendations: Vickers Pumpentest

Application: Industry

RAVENOL SCR 100 Screw Kompressorenöl is optimal alloyed, has a high performance level and a wide application area of the whole industry. It is characterised by a good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

Application instructions

RAVENOL SCR 100 Screw Kompressorenöl is used in screw compressors.

Vickers-Pump Test, FZG-Test A 8,3/90: 12th load level is reached. Refer to the manual.

Characteristics

- High performance level
- Very good viscosity temperature behaviour
- High aging resistant
- Excellent corrosion protection
- Solid corrosion protection
- Neutrality of sealing materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	11,2	DIN 51562-1
Viscosity at 40 °C	mm ² /s	100,2	DIN 51562-1
Viscosity Index VI		98	DIN ISO 2909
Density at 20 °C	kg/m ³	875,0	EN ISO 12185
Flashpoint	°C	264	DIN EN ISO 2592
Pourpoint	°C	-21	DIN ISO 3016