



RAVENOL Vakuumpumpenoel ISO VG 32

Kategorie: Industrial oil

Artikelnummer: 1330704

Viscosity: 32

Oil type: Mineral

Recommendations: Alcatel 100, Alcatel 119, Alcatel 120, Balzers P3, Becker Vakuumpumpen, Beckmann 19, BUSCH VM, BUSCH VMH, DIN 51506 VC, Edwards Ultragrade 19, Fisherbrand 19, Hyvac 93055, ISO 6743-3 DVA und DVC, Kinney Type A, Leybold-Heraeus 175, PVR Rotant, SAVANT SPO-1, Ulvac 100

Application: Industry



RAVENOL Vakuumpumpenoel ISO VG 32 is optimum alloyed and high level performance industrial oil with a wide range of applications throughout the industry. It is characterized by good viscosity-temperature behavior, high resistance to aging and reliable corrosion protection. Effective additives ensure even under extreme loads an excellent wear protection. Neutral behavior towards sealing materials.

1L | 1330704-001

5L | 1330704-005

10L | 1330704-010

20L | 1330704-020

20L | 1330704-B20

60L | 1330704-060

208L | 1330704-208

Application instructions

RAVENOL Vakuumpumpenoel ISO VG 32 is suitable for the lubrication of vacuum pumps (rotary vane pumps, diffusion pumps, turbo pumps), where mineral oils are required, as well as for mist lubrication and crankcase.

RAVENOL Vakuumpumpenoel ISO VG 32 oil can be used very well for the lubrication of crankcases.

Characteristics

- High performance level
- Very good viscosity-temperature behavior
- High resistance to aging
- Excellent wear protection
- Reliable corrosion protection
- Neutral to seal materials

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellgelb	VISUELL
Viscosity at 100 °C	mm ² /s	5,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	32,1	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Density at 20 °C	kg/m ³	848,0	EN ISO 12185
Flashpoint	°C	224	DIN EN ISO 2592
FZG-Test A/8.3/90 Damage loading step	%wt.	12	DIN 51354/2
Pourpoint	°C	-30	DIN ISO 3016