



RAVENOL Vakuumpumpenoel ISO VG 68



1L | 1330706-001

5L | 1330706-005

20L | 1330706-020

20L | 1330706-B20

60L | 1330706-060

208L | 1330706-208

Kategorie: Industrial oil

Artikelnummer: 1330706

Viscosity: 68

Specifications: 2 HLP, DIN 51506 VC, DIN 51524-2

Oil type: Mineral

Recommendations: AFNOR NFE 48-603 HM, AFNOR NFE 48-603 HV, Vickers Vane Pump

Application: Industry

RAVENOL Vakuumpumpenoel ISO VG 68 is optimum alloyed and high level performance industrial oil with a wide range of applications throughout the industry. It is characterized by good viscosity-temperature behavior, high resistance to aging and reliable corrosion protection. Effective additives ensure even under extreme loads an excellent wear protection. Neutral behavior towards sealing materials.

Application instructions

RAVENOL Vakuumpumpenoel ISO VG 68 is suitable for the lubrication of vacuum pumps (rotary vane pumps, diffusion pumps, turbo pumps), where mineral oils are required, as well as for mist lubrication and crankcase.

RAVENOL Vakuumpumpenoel ISO VG 68 oil pumps can be used very well for the lubrication of crankcases. This vacuum pump oil should not be used in systems with silver or silver alloys.

Characteristics

- High performance level
- Very good viscosity-temperature behavior
- High resistance to aging
- Excellent wear protection
- Reliable corrosion protection
- Very good oxidation stability
- Very good demulsification
- Excellent air release, which largely eliminates foam formation
- Neutral from over plastic seals
- Low pour point

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellgelb	VISUELL
Viscosity at 100 °C	mm ² /s	9,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	68,0	DIN 51562-1
Viscosity Index VI		106	DIN ISO 2909
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Flashpoint	°C	256	DIN EN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016