



# RAVENOL Getriebeoel CLP 32

**Kategorie:** Industrial oil

**Artikelnummer:** 1332104

**Viscosity:** 32

**Specifications:** DIN 51517-3

**Oil type:** Mineral

**Recommendations:** AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes, US Steel 224

**Application:** Industry



20L | 1332104-020

## RAVENOL Getriebeoel CLP 32

is a high quality, mineral-based gear oil formulated with selected high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

## RAVENOL Getriebeoel CLP 32

has a low pour point and therefore a very good cold behaviour.

## Application instructions

### RAVENOL Getriebeoel CLP 3

can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

## Characteristics

- A very good, stable high-pressure absorption capacity under shock loads.
- Resistant properties at elevated temperatures
- A good anti-rust and anti-corrosion effect
- Excellent wear protection
- A very good effect against foam formation
- A low pour point
- A very good cold behavior

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	6,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	34,6	DIN 51562-1
Viscosity Index VI		119	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	854,0	EN ISO 12185
Flashpoint	°C	205	DIN EN ISO 2592
Pourpoint	°C	-30	DIN ISO 3016