



RAVENOL Getriebeöl CLP 46



20L | 1332105-020
208L | 1332105-208

Kategorie: Industrial oil

Artikelnummer: 1332105

Viscosity: 46

Specifications: DIN 51517-3

Oil type: Mineral

Recommendations: AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes, US Steel 224

Application: Industry

RAVENOL Getriebeöl CLP 46 is a high quality, mineral-based gear oil formulated with selected high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity. has a low pour point and therefore a **RAVENOL Getriebeöl CLP 46** has a low pour point and therefore a very good cold behaviour.

Application instructions

RAVENOL Getriebeöl CLP 46 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Characteristics

- A very good, stable high-pressure absorption capacity under shock loads.
- Resistant properties at elevated temperatures
- A good anti-rust and anti-corrosion effect
- Excellent wear protection
- A very good effect against foam formation
- A low pour point
- Very good cold behavior

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	7,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	44,8	DIN 51562-1
Viscosity Index VI		114	DIN ISO 2909
Density at 20 °C	kg/m ³	857	EN ISO 12185
Flashpoint	°C	224	DIN EN ISO 2592
Pourpoint	°C	-30	DIN ISO 3016