



RAVENOL Getriebeoel CLP 100

Kategorie: Industrial oil

Artikelnummer: 1332107

Viscosity: 100

Specifications: DIN 51517-3

Oil type: Mineral

Recommendations: AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, FZG 12, S-200 Oxidation Tubes, US Steel 224, ZF TE-ML 04H

Application: Industry

RAVENOL Getriebeoel CLP 100 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeoel CLP 100 has a low pour point and therefore a very good cold behaviour.



20L | 1332107-020

208L | 1332107-208

1000L | 1332107-700

Application instructions

RAVENOL Getriebeoel CLP 100 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Characteristics

- A very good, stable high-pressure impact capacity
- Resistant characteristics at high temperatures
- A good rust and corrosion impeding effect
- Excellent wear protection
- Very good anti-foaming characteristics
- A low pour point
- Very good cold behaviour

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	11,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	106,3	DIN 51562-1
Viscosity Index VI		106	DIN ISO 2909
Density at 20 °C	kg/m ³	875,0	EN ISO 12185
Flashpoint	°C	242	DIN EN ISO 2592
Pourpoint	°C	-21	DIN ISO 3016