



# RAVENOL Getriebeoel CLP 320



**Kategorie:** Industrial oil

**Artikelnummer:** 1332110

**Viscosity:** 320

**Specifications:** DIN 51517-3

**Oil type:** Mineral

**Recommendations:** AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes, US Steel 224

**Application:** Industry

**RAVENOL Getriebeoel CLP 320** is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

**RAVENOL Getriebeoel CLP 320** has a low pour point and therefore a very good cold behaviour.

- 20L | 1332110-020
- 20L | 1332110-B20
- 60L | 1332110-060
- 208L | 1332110-208
- 1000L | 1332110-700

## Application instructions

**RAVENOL Getriebeoel CLP 320** can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

## Characteristics

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures
- A good rust and corrosion impeding effect
- Excellent wear protection
- Very good anti-foaming characteristics
- A low pour point
- Very good cold behaviour

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	24,3	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	327,6	DIN 51562-1
Viscosity Index VI		95	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	895,0	EN ISO 12185
Flashpoint	°C	244	DIN EN ISO 2592
Pourpoint	°C	-9	DIN ISO 3016