



RAVENOL Mehrzweckfett OML

Kategorie: Grease

Artikelnummer: 1340101

Specifications: DIN 51502: K2K-30, ISO 6743-9: ISO-L-XCCEA2

Application: Industry, Passenger car, Truck, Agricultural machinery

RAVENOL Mehrzweckfett OML is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Mehrzweckfett OML has an extreme mechanical stability and a very low friction value. Therefore it can be transported easily.



Application instructions

RAVENOL Mehrzweckfett OML is used for the lubrication of easy loaded antifriction bearings and machine components. It is also suited as multipurpose lubrication grease for vehicles.

Characteristics

- Universal use, multipurpose characteristic for a mixed car pool
- Extreme shear stability
- Excellent corrosion protection
- Excellent wear protection
- Very good mechanical and chemical stability
- Very good aging resistant
- Good pumpability, even at low temperatures

5L | 1340101-005

15L | 1340101-015

100L | 1340101-100

180L | 1340101-180

400L | 1340101-400

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellbraun	VISUELL
Dropping Point	°C	>180	DIN ISO 2176
Thickener		Lithium-Komplekseifen	DIN 51757
VKA Pressure Carrying Capacity	N	2000 - 2200	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	265-295	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-30 / +120	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	130	DIN 51562-1
Corrosion (SKF Emscor dist. Water)	Korr. Grad	1	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	130	DIN 51757
NLGI-Class		2	DIN 51818
Product Classification		K2K-30	DIN 51502