



RAVENOL Wälzlagerfett LI-86

Kategorie: Grease

Artikelnummer: 1340105

Specifications: DIN 51502: K3K-30, ISO 6743-9: ISO-L-XCCFA3

Application: Industry, Passenger car, Truck, Agricultural machinery



RAVENOL Wälzlagerfett LI-86 is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Wälzlagerfett LI-86 is walk stable, stain-resistant and water-repellent.

RAVENOL Wälzlagerfett LI-86 offers excellent adhesion to metal.

Application instructions

RAVENOL Wälzlagerfett LI-86 is suitable for lubrication of all types of vehicle parts and industrial machines. Usable for lubrication of ball and roller bearings. Particularly recommended for chassis lubrication, construction machines and agricultural equipment also for use under tropical conditions.

Characteristics

- Universal use, multipurpose characteristic for a mixed car pool
- Extreme shear stability
- Excellent corrosion protection
- Very good mechanical and chemical stability
- Very good aging resistant
- Good pump output also at low temperatures

5L | 1340105-005

15L | 1340105-015

180L | 1340105-180

400L | 1340105-400

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellbraun	VISUELL
Dropping Point	°C	>190	DIN ISO 2176
Thickener		Lithium-Komplekseifen	DIN 51757
VKA Pressure Carrying Capacity	N	2000 - 2200	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	220-250	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-30 / +130	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	130	DIN 51562-1
Corrosion (SKF Emscor dist. Water)	Korr. Grad	1	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	150	DIN 51757
NLGI-Class		3	DIN 51818
Product Classification		K3K-30	DIN 51502