



RAVENOL KFZ-Fließfett ZSA

Kategorie: Grease

Artikelnummer: 1340107

Specifications: DIN 51502: GP00K-30, ISO 6743-9: ISO-L-XCCEB00

Approvals: MAN 283 Li-P 00/000, MB -Freigabe 264.0

Recommendations: DTFR 33B100 (MB 264.0)

Application: Agricultural machinery, Passenger car, Truck

RAVENOL KFZ-Fließfett ZSA is a lithium saponified EP flow grease for mobile central lubricating equipment.



5L | 1340107-005

15L | 1340107-015

180L | 1340107-180

Application instructions

RAVENOL KFZ-Fließfett ZSA is recommended by Willy Vogel, Mercedes-Benz and MAN for central lubricating equipment.

Characteristics

- Very good thermic stability
- Very good adhesion on metallic surfaces
- Excellent pump output, also at low temperatures
- Very good corrosion and oxidation protection
- Extreme shear stability
- Can be transported in case of changing climatically conditions over long distances and small section

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		grün	VISUELL
Dropping Point	°C	185	DIN ISO 2176
Thickener		Lithium-Komplekseifen	DIN 51757
VKA Pressure Carrying Capacity	N	unter 2000	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	400-430	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-30 / +120	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	40	DIN 51562-1
Corrosion (SKF Emscor dist. Water)	Korr. Grad	1	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	120	DIN 51757
NLGI-Class		00	DIN 51818
Product Classification		GP00K-30	DIN 51502