



# RAVENOL Polfett - Säureschutzfett

**Kategorie:** Grease

**Artikelnummer:** 1340115

**Specifications:** DIN 51502: K2K-30, ISO 6743-9: ISO-L-XCCEA2

**Application:** Industry, Passenger car, Truck, Motorcycle, Marine, Agricultural machinery



**RAVENOL Polfett-Säureschutzfett** is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

**RAVENOL Polfett-Säureschutzfett** has an extreme mechanical stability.

## Application instructions

**RAVENOL Polfett-Säureschutzfett** is used for the protection of contacts and metal parts against corrosion caused by aggressive media (acids).

100L | 1340115-100

## Characteristics

- Extreme shear stability
- Very good mechanical and chemical stability
- Excellent wear protection
- Very good aging resistant
- Excellent corrosion protection
- Good pumpability, even at low temperatures

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellbraun	VISUELL
Dropping Point	°C	>180	DIN ISO 2176
Thickener		Lithium-Komplekseifen	DIN 51757
VKA Pressure Carrying Capacity	N	2000 - 2200	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	265-295	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-30 / +120	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm <sup>2</sup> /s	130	DIN 51562-1
Corrosion (SKF Emscor dist. Water)	Korr. Grad	1	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	130	DIN 51757
NLGI-Class		2	DIN 51818
Product Classification		K2K-30	DIN 51502