



RAVENOL LKW FETT BLAU

Kategorie: Grease

Artikelnummer: 1340117

Specifications: DIN 51502: KP2N-30, ISO 6743-9: ISO-L-XCDEB2, VOLVO STD „Lubricating grease 97720“

Approvals: MAN 283 Li-P2, MB -Freigabe 267.0, DTFR 33B120

Recommendations: VW/Audi G 052 180 A1

Application: Agricultural machinery, Truck



5L | 1340117-005

15L | 1340117-015

180L | 1340117-180

400L | 1340117-400

RAVENOL LKW FETT BLAU is a lithium saponified multipurpose grease on mineral basis with oxidation and corrosion protective additives.

Because of its special additivation **RAVENOL LKW FETT BLAU** has an excellent pressure absorption capacity, excellent corrosion protection characteristics and a superior mechanical stability.

Application instructions

RAVENOL LKW FETT BLAU is used for the lubrication of high loaded friction and antifriction bearings of trucks and construction machines even under the influence of humidity, vibration and shock loading. Functional range from - 30°C up + 125°C (maximum + 140°C). NLGI class 2. Extended lubrication intervals.

Characteristics

- Extreme shear stability
- Excellent corrosion protection
- Very good mechanical and chemical stability
- Very good aging resistance
- Good pump output also at low temperatures

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
Dropping Point	°C	220	DIN ISO 2176
Thickener		Lithium-Komplekseifen	DIN 51757
VKA Pressure Carrying Capacity	N	2200-2400	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	265-295	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-30 / +140	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	220	DIN 51562-1
Corrosion (SKF Emscor dist. Water)	Korr. Grad	0	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	220	DIN 51757
NLGI-Class		2	DIN 51818
Product Classification		KP2N-30	DIN 51502