



RAVENOL Hot Red Grease HRG 3

Kategorie: Grease

Artikelnummer: 1340122

Specifications: DIN 51502: KP3P-25, ISO 6743-9: ISO-L-XBEEB3

Application: Industry, Passenger car, Truck



5L | 1340122-005

15L | 1340122-015

180L | 1340122-180

400L | 1340122-400

RAVENOL Hot Red Grease HRG 3 is a red lithium complex soap lubricating grease on the basis of high quality base oils. Excellent work resistance, rust and corrosion protection. Application for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures. Particularly recommended for the lubrication of wheel bearings on commercial vehicles and for high-speed passenger car wheel bearings.

Application instructions

RAVENOL Hot Red Grease HRG 3 is used for the lubrication of roller and friction bearings under extreme pressure at high bearing temperatures.

RAVENOL Hot Red Grease HRG 3 is particularly recommended for the lubrication of commercial vehicles and for high-speed passenger car wheel bearings.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		rot	VISUELL
Dropping Point	°C	>260	DIN ISO 2176
Thickener		Lithium-Komplexseifen	DIN 51757
VKA Pressure Carrying Capacity	N	2600 - 2800	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	220-250	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-25 / +160	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	150	DIN 51562-1
Corrosion (SKF Emscor dist. Water)	Korr. Grad	0	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	200	DIN 51757
NLGI-Class		3	DIN 51818
Product Classification		KP3P-25	DIN 51502