



20L | 1350131-020

* RAVENOL Calibration Fluid 2.5

Kategorie: Industrial oil

Artikelnummer: 1350131

Recommendations: Bosch VS 15665-OL-CV, ISO 4113-CV-AW, Lucas CAV, MAN, MB DBL 6513, VW

Application: Industry

RAVENOL Calibration Fluid 2.5 is a low viscosity test fluid for the calibration of diesel injection pumps with a very close viscosity tolerance. It is noted for its excellent wear-, corrosion-protection and low foaming tendency. The product is also suitable for use as corrosion protection oil for the internal preservation or conservation of fuel systems from MTU.

Application instructions

RAVENOL Calibration Fluid 2.5 is used as a test fluid for the calibration of diesel injection pumps from Bosch (VS 15665-OL), MTU, MAN and Volkswagen. The product is also suitable for use as corrosion preventive oil for the internal preservation or conservation of fuel systems from MTU.

Characteristics

- Excellent wear protection
- Excellent corrosion protection
- Low tendency to foam

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Initial Boiling Point	°C	232	DIN 51751
Final Boiling Point	°C	265	DIN 51751
Colour		farblos	VISUELL
Viscosity at 20 °C	mm ² /s	3,85	DIN EN ISO 3104
Viscosity at 40 °C	mm ² /s	2,52	DIN EN ISO 3104
Cloudpoint	°C	-28	ASTM D2500
Steel corrosion		0-A	DIN ISO 7120
Corrosion test (humidity chamber)		6x0	ASTM D1748
Density at 20 °C	kg/m ³	821	EN ISO 12185
Flashpoint	°C	105	DIN 51757
Copper strip corrosion		1	DIN EN ISO 2160