



RAVENOL Bettbahnöl 32

Kategorie: Industrial oil

Artikelnummer: 1350374

Viscosity: 32

Specifications: AFNOR E 60-203 L-G/HG, DIN 51502: CGLP, DIN 51517-3, DIN 51524-2, GB 11118.1-94 L-HG/HM, ISO 11158 HG, HM, ISO 19378 GA, GB, ISO 6743-13 GA, GB, ISO 6743-6 CKC, SAE MS 1007 Typ E, SH/T 0361-98 L-G

Oil type: Mineral

Recommendations: Eaton Vickers M-2950-S, Fives Cincinnati P-53, GM LS-2 LW-03-1-04

Application: Industry



208L | 1350374-208

RAVENOL Bettbahnoel 32 is mineral slide way oil CGLP.

RAVENOL Bettbahnoel 32 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 32 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 32 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application instructions

RAVENOL Bettbahnoel 32 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Wear protection and pressure absorption capacity
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	5,75	DIN 51562-1
Viscosity at 40 °C	mm ² /s	31,9	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Density at 20 °C	kg/m ³	854,0	EN ISO 12185
Flashpoint	°C	216	DIN EN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016