



RAVENOL Bettbahnoel 68

Kategorie: Industrial oil

Artikelnummer: 1350376

Viscosity: 68

Specifications: DIN 51502: CGLP, DIN 51517-3, DIN 51524-2

Oil type: Mineral

Application: Industry



5L | 1350376-005

20L | 1350376-020

60L | 1350376-060

208L | 1350376-208

RAVENOL Bettbahnoel 68 is mineral slide way oil CGLP.

RAVENOL Bettbahnoel 68 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 68 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 68 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application instructions

RAVENOL Bettbahnoel 68 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	8,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	66,6	DIN 51562-1
Viscosity Index VI		104	DIN ISO 2909
Density at 20 °C	kg/m ³	869,0	EN ISO 12185
Flashpoint	°C	256	DIN EN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016