



20L | 1350378-020
208L | 1350378-208

RAVENOL Bettbahnöl 220

Kategorie: Industrial oil

Artikelnummer: 1350378

Viscosity: 220

Specifications: DIN 51502: CGLP, DIN 51517-3, DIN 51524-2

Oil type: Mineral

Application: Industry

RAVENOL Bettbahnoel 220 is mineral slide way oil CGLP.

RAVENOL Bettbahnoel 220 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnoel 220 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnoel 220 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application instructions

RAVENOL Bettbahnoel 220 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb	VISUELL
Viscosity at 100 °C	mm ² /s	18,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	216,7	DIN 51562-1
Viscosity Index VI		96	DIN ISO 2909
Density at 20 °C	kg/m ³	890,0	EN ISO 12185
Flashpoint	°C	250	DIN EN ISO 2592
Pourpoint	°C	-15	DIN ISO 3016