



RAVENOL Pressure Washing Concentrate

Kategorie: Car care products

Artikelnummer: 1360007



1L | 1360007-001

5L | 1360007-005

10L | 1360007-010

30L | 1360007-030

208L | 1360007-208

RAVENOL Pressure Washing Concentrate is a versatile, high quality, concentrate suitable for use on vehicles of all types including motorcycles and mopeds, as well as for effective cleaning of rubber flooring, stone and flagged flooring, patios, tarpaulins, awnings, plastics, tiles and more.

RAVENOL Pressure Washing Concentrate is formulated to remove even the most resistant dirt and grime and leave vehicles with an as-new shine.

Application instructions

Shake container well before use, then pour **RAVENOL Pressure Washing Concentrate** into pressure washer tank and dilute according to intended use and as specified by the equipment manufacturer. For heavily soiled areas spray initially with neat concentrate and allow to act briefly, then wash off with a pressure washer containing diluted product as normal.

RAVENOL Pressure Washing Concentrate is economical to use, since it is a highly concentrated formulation which can be diluted with water up to 1:20.

Examples of recommended dilution rates:

Workshop floors: 1:1 to 1:20 depending on level of contamination; verdigris and algae: 1:5; underbody wash: 1:10; wheel rim cleaning: 1:1 to 1:3; workshop tools: 1:10; mopeds and motorcycles: 1:20; tarpaulins and awnings: 1:5

Please check material compatibility prior to use in an inconspicuous area.

RAVENOL Pressure Washing Concentrate is approved, tried and tested in units of: Kärcher, Lavor, Nilfisk Alto, Portotecnica, Kränzle, Delvir, Comet

Characteristics

- effectively removes adherent dirt, grease, oils and fat residues from all types of surfaces.
- is gentle on the material despite the high cleaning efficiency, and compatible for use on paints, plastics and glass surfaces
- is a mildly alkaline cleaning concentrate adjusted with cleansing substances and surfactants.
- is free from formaldehyde and AOX.
- Special demulsifiers ensure speedy separation of oil and water in oilseparation equipment.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		klar, bräunlich	VISUELL
Density at 20 °C	kg/m ³	1068	
pH - value		10,9-11,5 (1%ige Lösung)	