



RAVENOL Copper-Spray

Kategorie: Car care products

Artikelnummer: 1360016

Application: Hobby and garden



0.4L | 1360016-400

RAVENOL Copper-Spray is a high-performance, high-temperature-resistant special lubricant for demanding industrial and automotive applications as well as for many home applications.

RAVENOL Copper-Spray provides effective protection against corrosion, wear, and material-related damage such as seizing or cold welding. The perfect combination of the finest copper powder, selected additives, and other solid lubricants ensures excellent adhesion and exceptionally high thermal and chemical stability.

RAVENOL Copper-Spray ensures a permanently effective protective and lubricating coating that works reliably even under exposure to salt water.

RAVENOL Copper-Spray is ideal for the following applications:

Flanges, exhaust systems, brake systems, fittings, furnaces, steam pipes, brake systems (ONLY WITHOUT ABS/ASR), and connections in maritime or saltwater environments.

Application instructions

RAVENOL Copper-Spray should only be used on dry and clean surfaces. Remove any lubricant residues beforehand. Shake the can thoroughly before use and ensure it is held upright or at a slight angle during application.

RAVENOL Copper-Spray should be sprayed on from a distance of 20-30 cm. Due to its high active ingredient content, it can be used sparingly. A second spray head is integrated into the cap for more precise application.

Note:

Do not store under pressure, above +50°C, or in direct sunlight.

Not suitable for brake systems with ABS or ASR. This may lead to malfunction of the sensors.

Characteristics

- Versatile application options

- Good surface adhesion and abrasion resistance
- High temperature resistance
- Anti-corrosive, prevents fretting corrosion and seizing
- Eliminates squeaking and creaking
- High active ingredient content, economical to use
- Free of lead components
- High oxidation stability and salt water resistance

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
		Kupfer / Copper	VISUELL
Working Temperature	°Celsius	-100 to +1200	