RAVENOL RV-46 Multi Spray

Kategorie: Car care products

Artikelnummer: 1360306

0.4L | 1360306-400

RAVENOL RV-46 Multi Spray sneaks under dirt and loosens rusted and stuck components such as screws, nuts, etc. It penetrates deep into threads and mechanical connections, loosens rust at selected spots and then protects against further corrosion.

RAVENOL RV-46 Multi Spray lubricates hinges, guides, bearings and many types of joints and couplings while effectively eliminating squeaking and creaking noises. It displaces moisture from electrical contacts and prevents leakage currents.

RAVENOL RV-46 Multi Spray cleans soiled metal surfaces and leaves behind a long-lasting, ultra-thin film that neither smears nor sticks and does not attract dust. This film protects and maintains tools, machines and electrical and mechanical equipment while keeping them in good working order.

RAVENOL RV-46 Multi Spray offers a versatile and reliable solution for daily use in the workshop and at home thanks to its specialized formula and excellent penetrating properties. Its formulation is gentle on paint, plastics, seals and other solid surfaces, should it get onto surrounding components during application.

Application instructions

RAVENOL RV-46 Multi Spray must be shaken thoroughly before use and the can must be held upright or slightly inclined during application.

RAVENOL RV-46 Multi Spray is sprayed on at a distance of approx. 5 cm and left to work for at least 30 seconds. In case of a cleaning application, wipe off with a cloth afterwards. Only use on parts or components that are not under power during application.

Note:

Do not store under pressure, above +50°C or in direct sunlight.

Characteristics

- Versatile application range
- Cleans and protects
- Anti-corrosive
- Loosens and frees stuck components
- Sneaks under dirt, resin, tar and others
- Eliminates squeaking and creaking
- Gentle on paintwork, plastics and seals
- Silicone-free
- Shelf life of 24 months

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelblich, transparent	VISUELL
Working Temperature	°Celsius	-50 bis +210	---
Odour		Vanille	---
Kinematic Viscosity (Base Oil) at 40 °C	mm²/s	21	---