



# RAVENOL TTC Hot Climate -15°C Protect C11

RAVENOL TTC Hot Climate -15°C Protect C11 **Kategorie:** Radiator antifreeze

**1.5L | 1410106-150**  
**5L | 1410106-005**  
**20L | 1410106-020**  
**60L | 1410106-060**  
**208L | 1410106-208**  
**1000L | 1410106-700**

**Artikelnummer:** 1410106

**Recommendations:** AFNOR R15-601, ASTM D1384, ASTM D2570, ASTM D2809, ASTM D3306, ASTM D4985, ASTM D6210 Type 1-FF, British Standard BS 6580 (GB), Chrysler MS-7170, CUNA NC 956-16 (Italien), Fiat 9.55523, Fiat PARAFU 11, Ford WSS-M97B51-A1, IVECO 18-1830, JIS K 2234 (Japan), MAN 324 NF, O Norm V 5123 (Österreich), SAE J1034, Suzuki, UNE 25-361 (Spanien), VW TL 774-C (entspricht G11)

**Application:** Oldtimer, Passenger car, Truck, Motorcycle, Marine, Agricultural machinery, Industry

**RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without phosphates, nitrites and amines. This product is formulated based on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why manufacturers subject antifreeze to lengthy corrosion and cavitation tests.

## Application instructions

**RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines. Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL TTC Trad. Techn. Coolant HOT CLIMATE -15°C** to radiator to fill line.

## Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb-grün fluoreszent	VISUELL
Density at 20 °C	kg/m <sup>3</sup>	1045,0	EN ISO 12185
Freezing point	°C	-15	ASTM D1177
pH - value at 20 °C		7,0-8,4	ASTM D1287