



# RAVENOL OTC Premix -40°C Protect C12+

**Kategorie:** Radiator antifreeze

**Artikelnummer:** 1410112



**Recommendations:** DAF 74002, Deutz DQC CB-14, DTFR 29C110 (MB 325.3), DTFR 29D110 (MB 326.3), Ford 1336797, Ford 1336807, Ford 1365305, Ford WSS-M97B44-D (ab Modell 1999), Jaguar JLM 209722, Jaguar Land Rover STJLR.651.5003, Land Rover STC50529, MAN 324 SNF, MB 325.3, MB 326.3 (Premix), Mitsubishi 0103044, Mitsubishi 0103045, Mitsubishi MZ311986, Opel/GM 6277 M, Opel/GM B0401065, Porsche, SAE J1034, Toyota 00272-1LLAC, Toyota 08889-00115, Toyota 08889-01005, Toyota 08889-80014, Toyota 08889-80015, VOLVO 9437650, VOLVO 9437651, VOLVO VCS (STD 418-0001), VW G 012 A8F M1, VW G 012 A8F M8, VW G 012 A8F M9, VW TL 774-F (entspricht G12+), VW/Audi TL 774-D (entspricht G12+)

**Application:** Industry, Passenger car, Truck, Marine, Agricultural machinery

**RAVENOL OTC Organic Techn. Coolant Premix -40°C** is a ready-to-use, prediluted with water, eco-friendly 1.2- Ethanediol (monoethylene glycol) based silicate, borate, nitrite, amine and phosphate-free coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. This product is formulated based on a proven inhibitor development with the organic additive technology OAT as an extended life coolant.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection. That is why manufacturers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL OTC Organic Techn. Coolant Premix -40°C** protects the cooling system from rust, frost, and in summer, from overheating.

## Application instructions

**RAVENOL OTC Organic Techn. Coolant Premix -40°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL OTC Organic Techn. Coolant Premix -40°C** to radiator to fill line.

**RAVENOL OTC Organic Techn. Coolant Premix -40°C** can also be used as a "ready for use" dilution in geothermal probes and geothermal collectors as recommended list of LAWA (Federal / State Working Group on Water in Germany). **RAVENOL OTC Organic Techn. Coolant Concentrate** is included in the list of recommendations of the LAWA for water management requirements for geothermal probes and geothermal collectors.

- 1.5L | 1410112-150
- 5L | 1410112-005
- 20L | 1410112-020
- 20L | 1410112-B20
- 60L | 1410112-060
- 208L | 1410112-208
- 1000L | 1410112-700

## Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection for all metals and metal alloys used in coolsystems, including aluminium
- Prevents sediments and foaming in the cooling system
- Compatible with elastomers used in automotive radiators
- Can be mixed with other coolant types

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		lila	VISUELL
Density at 20 °C	kg/m <sup>3</sup>	1070,0	EN ISO 12185
Freezing point	°C	-40	ASTM D1177
pH - value at 20 °C		7,5 - 8,5	ASTM D1287