



RAVENOL TTC COLD CLIMATE -60°C Protect C11

Kategorie: Radiator antifreeze

Artikelnummer: 1410140

Recommendations: AFNOR R15-601, ASTM D1384, ASTM D2570, ASTM D2809, ASTM D3306, ASTM D4985, ASTM D6210 Type 1-FF, British Standard BS 6580 (GB), Chrysler MS-7170, CUNA NC 956-16 (Italien), Fiat 9.55523, Fiat PARAFU 11, Ford WSS-M97B51-A1, IVECO 18-1830, JIS K 2234 (Japan), MAN 324 NF, O Norm V 5123 (Österreich), SAE J1034, Suzuki, UNE 25-361 (Spanien), VW TL 774-C (entspricht G11)

Application: Passenger car



- 1.5L | 1410140-150
- 5L | 1410140-005
- 20L | 1410140-020
- 60L | 1410140-060
- 208L | 1410140-208

RAVENOL TTC COLD CLIMATE -60°C is an ready to use, prediluted eco-friendly 1.2- Ethanediol (monoethylene glycol) based nitrite, amine and phosphate-free coolant for cooling circuits in combustion engines which provides maintenance-free corrosion and frost protection. The product is formulated as a long-term coolant based on a proven inhibitor development. The product is suitable for regions with cold climate.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection. That is why manufacturers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL TTC COLD CLIMATE -60°C protects the cooling system from rust, frost, and in summer, from overheating.

Application instructions

RAVENOL TTC COLD CLIMATE -60°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines for regions with cold climate.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add **RAVENOL TTC COLD CLIMATE -60°C** to radiator to fill line.

RAVENOL TTC COLD CLIMATE -60°C can also be used according the mixing table.

Mix **RAVENOL TTC COLD CLIMATE -60°C** with distilled water (per mixing chart) and add. Allow engine and heater to warm up, add coolant to fill level.

Table of mixing ratios:

Antifreeze protection until	Parts Antifreeze	Parts Water
-25°C	50%	50%
-37°C	65%	35%

Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelb-grün fluoreszent	VISUELL
Density at 20 °C	kg/m ³	1110,0	EN ISO 12185
Freezing point	°C	-60	ASTM D1177
pH - value at 20 °C		8,0	ASTM D1287